





Smooth ride

The Challenger 650 aircraft's wing was designed to provide you with a restful flight experience.



Widest-in-class cabin

Larger seats, bigger monitors and the space to move around freely. Others simply don't measure up.



NextGen ready

The best equipped cockpit in its class and available Ka-band high-speed internet connectivity ensure you are always ahead of what's next.



Lowest direct operating costs

With class-leading economics, the Challenger 650 is the aircraft of choice among corporate flight departments and charter operators.



Most reliable by design

Count on this. With over 5 million flight hours, the Challenger 650 platform was designed to deliver on safety and peace of mind.



#1 in deliveries

Most successful large business jet platform of all time.

For more information, please visit

businessaircraft.bombardier.com

Challenger 650



CAPACITY

Passengers: Up to 12

ENGINES

GE CF34-3B MTO

Thrust: 9,220 lbf (41kN) Flat rated to ISA + 15°C

AVIONICS

- Rockwell Collins Advanced avionics suite with four large displays
- Dual Flight Management System with LPV and RNP approach capabilities
- Synthetic Vision System (SVS)
- MultiScan weather radar
- Dual Inertial Reference System (IRS)
- Dual SBAS/WAAS GPS

RANGE			AIRFIELD PERFORMANCE
Maximum range ⁽¹⁾	4,000 nm	7,408 km	Takeoff distance (SL, ISA, M
SPEED		MACH	Landing distance (SL, ISA, ty
Top speed		0.85	OPERATING ALTITUDE
High speed cruise		0.82	Maximum operating altitud
Typical cruise speed		0.80	Initial cruise altitude (MTOV

INTERIOR		
Cabin height	6 ft 0 in	1.83 m
Cabin width	7 ft 11 in	2.41 m
Cabin length ⁽²⁾	25 ft 7 in	7.80 m
EXTERIOR		
Length	68 ft 5 in	20.9 m
Wingspan	64 ft 4 in	19.6 m
Wing area	489 ft ²	45.4 m ²
Height	20 ft 8 in	6.3 m

., ISA, MTOW) 5,640 ft 1.720 m L, ISA, typical) 2,402 ft 732 m

JDE

altitude 41,000 ft 12,497 m (MTOW) 37,000 ft 11,278 m

WEIGHTS

48,300 lb	21,909 kg
48,200 lb	21,863 kg
38,000 lb	17,237 kg
32,000 lb	14,515 kg
27,150 lb	12,315 kg
20,000 lb	9,072 kg
4,850 lb	2,200 kg
	48,200 lb 38,000 lb 32,000 lb 27,150 lb 20,000 lb

The information in this document is proprietary to Bombardier Inc. or its subsidiaries. All specifications and data are approximate, may change without notice and subject to certain operating rules, assumptions and other conditions. The interior images shown are for information purposes only and may represent some optional configurations. This document does not constitute an offer, commitment, representation, quarantee or warranty of any kind and the configuration and performance of any aircraft shall be determined in a final purchase agreement. This document must not be reproduced or distributed in whole or in part to or by a third party. Bombardier shall be notified in writing of all the requests for permission to disclose. (1) Theoretical range with NBAA IFR Reserves, ISA, LRC, 6 pax /2 crew. Actual range will be affected by speed, weather, selected options and other factors. (2) From cockpit divider to aft most cabin without baggage compartment. MultiScan is a registered trademark of Rockwell Collins. Bombardier, Challenger and Challenger 650 are trademarks of Bombardier Inc. or its subsidiaries. © 2017 Bombardier Inc. All rights reserved.

